


Model	 =Electric	<b>BT30ERT</b> <b>BT30RT</b>	<b>BT28ERT</b> <b>BT28RT</b>	<b>BT26SERT</b> <b>BT26SRT</b>	<b>BT26ERT</b> <b>BT26RT</b>	<b>BT24ERT</b> <b>BT24RT</b>	<b>BA28ERT</b> <b>BA28RT</b>	<b>BA24ERT</b> <b>BA24RT</b>
Type	Telescopic Boom Lifts						Articulating Boom Lifts	
<b>Size</b>								
Max. Working Height	30.30m	28.60m	26.70m	26.32m	24.80m	28.10m	24.30m	
Max. Platform Height	28.30m	26.60m	24.70m	24.32m	22.80m	26.10m	22.30m	
Max. Horizontal Reach	22.40m	21.30m	19.20m	18.90m	17.30m	18.80m	16.50m	
Overall Length(Stowed) <b>A</b>	12.25m	11.66m	10.83m	10.82m	10.25m	11.83m	9.83m	
Overall Length(Transport)	11.96m	11.82m	11.12m	10.77m	10.81m	12.03m	10.03m	
Overall Width(Stowed) <b>B</b>	2.50m							
Overall Width(Transport)	2.28m							
Overall Height(Stowed) <b>C</b>	2.89m							
Overall Height(Transport)	2.60m							
Platform Size(Length×Width)	2.44m×0.9m							
Turntable Tailswing	1.61m							
Ground Clearance <b>D</b>	0.41m							
Wheelbase <b>E</b>	2.8m							
Turning Radius(Inside/Outside)	1.87m/3.22m							
Tyres	385/45-28							
Up And Over Clearance							9.14m	
Max. Down Probing Depth							6.61m	4.03m
<b>Performance</b>								
S.W.L.(Unrestricted/Restricted)	300kg/454kg	454kg				250kg	300kg	
Max. Occupants	3						2	
Gradeability	30% 45%	30% 45%	30% 45%	30% 45%	30% 45%	30% 45%	30% 45%	
Travel Speed(Stowed)	6km/h							
Travel Speed(Raised)	1.1km/h							
Max. Working Slope	X-5°/Y-5°							
Turret Rotation	360°Continuous							
Platform Rotation	180°							
Jib Movement	130°	135°	130°					135°
<b>Weight</b>								
Overall Weight	18900kg	18400kg	16800kg	16090kg	14300kg	18300kg	17100kg	
<b>Power</b>								
Lithium Battery	520Ah/80V		420Ah/80V			520Ah/80V	420Ah/80V	
Charger	80V/80A							
Diesel Engine	Deutz TD2.9 L4 55.4kW							
Hydraulic Tank	165L							

