

Platform

2.50 m X 5.35 m Platform (7.55 m extended)
 Single hydraulic powered deck extension
 Composite treated wooden floor
 Fold-down/drop-down handrails
 Self-closing gate
 Removable platform console box
 Platform console function status LED's¹
 Lanyard attach points
 Proportional drive control
 Load sensing system
 Two speed drive selection
 Hydraulic differential lock

Power & Transmission

Deutz D2011L04i (42kW) diesel engine
 Gull wing steel engine / valve compartment hoods
 Engine monitoring system with integral shut-down
 Hydraulic transmission
 Four wheel drive
 Drive disconnect/brake release

¹ Indicator LED lights on platform control console for tilt, high drive, lift, drive and overload interlocks.

Functional Equipment & Accessories

Nivolux self-levelling hydraulic jacks
 Steel mesh scissor arm guards
 315/80 R22.5 foam filled lug tread tyres
 Oscillating rear axle
 3 degree tilt indicator light with cut-out
 Ground control selector switch with key lock
 Full grease lubrication on all scissor arm bushings
 Scissor maintenance prop
 Manual descent system
 Hour meter
 Horn
 Travel alarm
 Lifting/tie down lugs

Available Options

AC cable to platform

JLG Industries Inc.
 Polaris Avenue 63
 2132 JH Hoofddorp
 The Netherlands
 Tel: +31 (0)23 565 5665
 Fax: +31 (0)23 557 2493
 e-mail address: europe@jlg.com
www.jlgeurope.com
 An Oshkosh Corporation Company

Printed in UK
 FORM No.: DS019-0208-500
 PART NO.: DS019-ENGLISH



210-25

A. Platform height - elevated	21.00 m
B. Platform height - lowered	3.00 m
C. Platform railing height	1.10 m
D. Stowed height (rails folded)	3.20 m
E. Platform size	2.50 m x 5.35 m
F. Platform length fully extended	7.55 m
G. Overall width	2.50 m
H. Overall length	5.75 m
I. Wheelbase	3.90 m
Ground clearance	0.26 m
Platform capacity	1,000 kg
Capacity on deck extension	800 kg
Lift/lower time	100 / 75 sec
Maximum drive height	21.00 m
Deck extension	Hydraulic
Machine weight ¹	15,000 kg
Maximum ground bearing pressure	5.0 kg/cm ²
Drive speed - high	2.3 km/h
Drive speed - elevated	0.5 km/h
Gradeability (4WD)	30%
Turning radius - inside	1.50 m
Turning radius - outside	6.20 m
Axle oscillation	0.15 m (±)
Tyres	315/80 R22.5 Foam Filled
Diesel engine	42 kW Deutz D2011L04i
Fuel tank capacity	90 L
Hydraulic system	325 L

¹Certain options or country standards may increase weight and/or dimensions.

